

```
version 12.4
no service pad
service timestamps debug datetime localtime
service timestamps log datetime localtime
service password-encryption
!
hostname ap
!
logging buffered 8192 debugging
!
aaa new-model
!
!
aaa authentication login default local
aaa authorization exec default local
!
aaa session-id common
clock timezone MET 1
clock summer-time MET recurring last Sun Mar 2:00 last Sun Oct 3:00
!
!
dot11 ssid xxxxxxxx
    authentication open
    authentication key-management wpa version 2
    guest-mode
    wpa-psk ascii 7 xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
!
dot11 network-map
power inline negotiation prestandard source
!
username xxxxxxxx privilege 15 password 7 xxxxxxxxxxxxxxxxxxxx
!
bridge irb
!
!
interface Dot11Radio0
no ip address
no ip route-cache
!
encryption mode ciphers aes-ccm
!
ssid xxxxxxxx
!
speed basic-1.0 basic-2.0 basic-5.5 basic-11.0 basic-6.0 basic-9.0 basic-12.0 basic-18.0 basic-24.0 basic-
36.0 basic-48.0 basic-54.0
station-role root
no dot11 extension aironet
bridge-group 1
bridge-group 1 subscriber-loop-control
bridge-group 1 block-unknown-source
no bridge-group 1 source-learning
```

```
no bridge-group 1 unicast-flooding
bridge-group 1 spanning-disabled
!
interface Dot11Radio1
no ip address
no ip route-cache
!
encryption mode ciphers aes-ccm
!
ssid xxxxxxx
!
no dfs band block
speed basic-6.0 basic-9.0 basic-12.0 basic-18.0 basic-24.0 basic-36.0 basic-48.0 basic-54.0
channel dfs
station-role root access-point
no dot11 extension aironet
bridge-group 1
bridge-group 1 subscriber-loop-control
bridge-group 1 block-unknown-source
no bridge-group 1 source-learning
no bridge-group 1 unicast-flooding
bridge-group 1 spanning-disabled
!
interface FastEthernet0
no ip address
no ip route-cache
duplex auto
speed auto
bridge-group 1
no bridge-group 1 source-learning
bridge-group 1 spanning-disabled
!
interface BVII
ip address 192.168.1.252 255.255.255.0
no ip route-cache
!
ip default-gateway 192.168.1.253
ip http server
ip http authentication aaa
no ip http secure-server
ip http help-path http://www.cisco.com/warp/public/779/smbiz/prodconfig/help/eag
bridge 1 route ip
!
!
line con 0
line vty 0 4
password 7 xxxxxxxxxxxx
!
snmp server 85.17.233.194
snmp broadcast client
end
```